

Ground-Water Modeling with Analytic Elements: cultivating understanding of ground water systems Part I, II

6/7/01

[Click here to start](#)

Table of Contents

Author: Stephen Kraemer

[Ground-Water Modeling with Analytic Elements:
cultivating understanding of ground water
systems Part I, II](#) **Email:** kraemer.stephen@epa.gov

Home Page:
<http://www.epa.gov/athens/software/whaem/index.html>

[Outline](#)

[II. AEM Basics](#)

[Groundwater Mechanics](#)

[Flow to a stream](#)

[Stretch domain](#)

[Until scales are equal](#)

[Plotted to scale: Flow is essentially horizontal
Dupuit-Forchheimer Flow Neglect resistance to
vertical flow Thus: heads are constant in the
vertical Advantage: You get rid of one dimension
in the differential equation](#)

[Mathematical formulation](#)

[Introduce Discharge Potential](#)

[Analytic Elements 101](#)

[Uniform Flow](#)

[One Well](#)

[Two Wells](#)

[Five Wells in a Row](#)

[Line-sink](#)

[Area-sink](#)

[Inhomogeneity](#)

[Advantages of AEM over Discrete Numerical
Models](#)

Ground-Water Modeling with Analytic Elements: cultivating *understanding* of ground water systems

Part I, II

Mark Bakker
Biological & Agricultural
Engineering, UGA
Athens, GA

Steve Kraemer
Ecosystems Research
Division, EPA
Athens, GA



The University of Georgia



Outline

I. Introduction

II. AEM Basics


III. AEM Applications

IV. Future


II. AEM Basics

Groundwater Mechanics


Head: elevation to which
water rises in a standpipe




Flow to a stream




Stretch domain



Until scales are equal



Plotted to scale:
Flow is essentially horizontal



Dupuit-Forchheimer Flow

Neglect resistance to vertical flow

Thus: heads are constant in the vertical

Advantage: You get rid of one dimension
in the differential equation

Mathematical formulation

- Darcy's law

$$q_x = -k \frac{\partial h}{\partial x} \quad q_y = -k \frac{\partial h}{\partial y}$$

- Continuity of vertically integrated flow

$$\frac{\partial}{\partial x} \left(kh \frac{\partial h}{\partial x} \right) + \frac{\partial}{\partial y} \left(kh \frac{\partial h}{\partial y} \right) = -N$$

Introduce Discharge Potential

$$\frac{\partial^2 \Phi}{\partial x^2} + \frac{\partial^2 \Phi}{\partial y^2} = -N$$


Confined flow: $\Phi = kHh$

Unconfined flow: $\Phi = \frac{1}{2} kh^2$


Analytic Elements 101

- Based on the superposition of **analytic functions**
- Each **analytic function** is an **analytic element**
- Each **analytic element** represents a **hydrogeologic feature** in the aquifer
- Each element has degrees of freedom, so that different boundary conditions can be met
- Initially developed by **Otto Strack**


Uniform Flow




One Well




Two Wells




Five Wells in a Row




Line-sink



Area-sink



Inhomogeneity



Advantages of AEM over Discrete Numerical Models

- No need for artificial boundaries
- More accurate, because solution is analytic (no discretization)
- Insight gained because every analytic element represents a hydrogeologic feature